Inspection camera for pipes from Ø 40 - 300 mm with 30 or 65 m cable length, with integrated software for documentation and large removable 10.4" touchscreen.

Product profile

KEY FEATURES

- Picture editing, change of camera settings and menu guidance via the 10.4" color-touchscreen
- Direct recording of pictures (JPG) or video (AVI, resolution 720 x 600) as well as editing options (e.g. documentation
- Fast data recording with integrated keyboard to mark, highlight and name damages
- Picture and video transmission via WiFi, Micro-HDMI, Mini-USB, SD-Card
- Livestream of picture and data via WiFi to the ROCAM 4 app
- Self-levelling and exchangeable camera heads
- Exchangeable reels for various working ranges
- New platform based battery technology















TECHNICAL DATA

Picture and video format: JPG / AVI (resolution 720 x 600)

Camera head: Ø 25 mm, waterproof with 8 LEDs Ø 30 mm, self-levelling and waterproof

with 10 LEDs

Ø 40 mm, self-levelling and waterproof

with 36 LEDs

Ø 40 - 100 mm (mini-module) Working range:

Ø 70 - 150 mm (30 mm camera head) Ø 100 - 300 mm (40 mm camera head)

Cable length: 30 m version

65 m version

8 m mini-module (optional)

Cable diameter: 7 mm (30 m und 65 m reel)

5.5 mm (mini-module)

Transmitter frequency: 33 kHz

Power supply: Li-lon battery 18 V/4 Ah

Main adaptor 110 - 230 V, 50 - 60 Hz

WiFi transmitter

Simple data transmission to mobile devices

Li-Ion battery 18V/4.0 Ah (same as ROMAX 4000)

Long battery operation time (up to 6 hours)

Digital metre count

Precise determination of distance to camera head

Exchangeable reel system

Large operating range from Ø 40 mm pipe diameter

30 m/8 m

Removable display unit with 10.4" color-touchscreen

Full functionality, even in confined spaces

Integrated speakers

Direct audio replay

Cover protected connections for SD-Card, Micro-Hdmi, Mini-USB



Locating with ROSCOPE module ROLOC PLUS



Please note: This machine cannot be upgraded to a 65m cable.

Integrated microphone Voice recording for

documentation possible

Set (No. 1500002613) includes: ROCAM 4 Plus - 30 m cable, Ø 30 mm camera head, guidance ball, accessory bag including location transmitter, USB-cable, pencil, RO BC14/36 battery charger, RO BP18/4, 4.0 Ah 18V Li-Power battery

No.

ROCAM 4 Plus - 30 m cable, 30 mm head, EU 1500002613 ROCAM 4 Plus - 30 m cable, 40 mm head, EU 1500002614











ROCAM 4 Plus - 65 m

Inspection camera for pipes from Ø 40 - 300 mm with 65 m cable length, with integrated software for documentation and large removable 10.4" touchscreen.
















Large operating range from Ø 40 mm pipe diameter



Transport trolley with extendible handle

Set (No. 1500002615) includes: ROCAM 4 Plus - 65 m cable w/ transport trolley, Ø 30 mm camera head, guidance ball, accessory bag including: location transmitter, USB-cable, pencil, RO BC14/36 battery charger, RO BP18/4, 4.0 Ah 18V Li-Power battery

Model No.

1500002615 ROCAM 4 Plus - 65 m cable, 30 mm head, EU ROCAM 4 Plus - 65 m cable, 40 mm head, EU 1500002616



New platform based battery

technology

Transport trolley with extendible handle



ROCAM 4 Plus mini module

Easy extension of the working range of the ROCAM 4 for pipes Ø 40 - 100 mm

Product profile

KEY FEATURES

- Professional inspection of small pipe diameters
- Easy handling due to Exchange reel system

TECHNISCHE DATEN

Camera head: Ø 25 mm, waterproof with 8 LED lights

Working range: Ø 40 - 100 mm 8 m / 16 m Cable length: Cable diameter: 5.5 mm

Model No.

ROCAM 4 Plus mini module, 16 m cable 1500003296



¹⁾ Complete terms and conditions at rothenberger.com/roservice. RO SERVICE+ only valid in participating countries.



